

## SPECIFICATIONS

### General Specifications

Item	Specification
<b>Brake Pads</b>	
Brake pad minimum thickness	3.0 mm (0.118 in)
Brake pad maximum thickness variation (pad-to-pad)	2.0 mm (0.079 in)
Brake pad maximum taper wear (in any direction)	3.0 mm (0.118 in)
<b>Brake Disc</b>	
Front brake disc minimum thickness	28.4 mm (1.11 in)
Minimum thickness to machine front brake disc	29.0 mm (1.14 in)
<b>Lubricant</b>	
High Performance DOT 3 Motor Vehicle Brake Fluid PM-1 (Canada CPM-1)	ESA-M6C25-A

### General Specifications (Continued)

Item	Specification
High Temperature Nickel Anti-Seize Lubricant XL-2	ESE-M12A4-A
Silicone Brake Caliper Grease and Dielectric Compound XG-3-A	ESE-M1C171-A
Brake Parts Cleaner PM-4	—

### Torque Specifications

Description	Nm	lb-ft	lb-in
Bleeder screw	10	—	89
Brake caliper anchor plate bolts	115	85	—
Brake caliper bolts	34	25	—
Brake caliper flow bolt	70	52	—
Brake disc shield bolts	20	15	—
Brake flexible hose bracket bolts	20	15	—
Brake line fittings	17	13	—